

EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S1	24	((user client) with identifier) same transaction same request same path and database	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/25 10:52
S2	17	((user client) with identifier) same transaction same request same path and database and default	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/25 10:52
S3	9	((user client) with identifier) same transaction same request same path and database and default and command	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 13:17
S14	17	(validat\$3 configur\$3) same (request transaction) same database same identifier and (default same (attribute field)) and path and (template rule) and xml	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 13:40
S15	1	(validat\$3 configur\$3) same (request transaction) same database same identifier and (default same (attribute field)) and path and (template rule) and xml and (pars\$3 same xml)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 13:20
S19	27	((validat\$3 configur\$3) with (request transaction) with database) and (default with (path directory attribute)) and xml and (transaction same request)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 14:16
S21	13	((validat\$3) same (request same transaction) same (identifier user)) and (default with (path directory attribute)) and xml	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 14:37
S22	1	((validat\$3) same (transaction) same query same (identifier user)) and (default with (path xpath directory attribute)) and xml	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 14:38

EAST Search History

S23	6	((validat\$3) same (input transaction) same query same (identifier user)) and (default with (path xpath directory attribute)) and xml	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 14:44
S24	7	user same pattern same (match\$3 validat\$3) same (default with (data path)) same (request input)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 14:53
S27	4	user same (request input) same ((pattern with match\$3) validat\$3) and (default with (data path) same (database with path))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 14:59
S31	35	(generat\$3 configur\$3 transform) with (request query) with (rule criteria) same (default with (data attribute value))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 15:38
S35	29	(generat\$3 configur\$3 transform) with (request query) with (rule criteria) and (default with (data attribute value)) and xml and (database same path)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 16:08
S39	42	((default near4 (data attribute value)) with (user identifier)) and xml and (database with path) and @ad<"20040101"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 16:28
S42	13	((default near2 (data attribute value)) near4 (client customer user identifier)) same database same (query request) and xml	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 16:42
S44	1	(request query) same transaction same (rule criteria) same (user near2 profile) and (default near2 (data path)) and @Ad<"20040101" and database	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/29 14:09

EAST Search History

S45	14	(request query) same (rule criteria) same (user near2 profile) and (default near2 (data path)) and @Ad<"20040101" and database	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 16:55
S47	8	user with default with database with path	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/08/28 16:56

sfg.lin@gmail.com | [My Account](#) | [Sign out](#)[Web](#) [Images](#) [Video](#)^{New!} [News](#) [Maps](#) [more »](#)

xml path sql query required default criteria sing

[Advanced Search](#)
[Preferences](#)**Web** Results 1 - 10 of about 23,300 for xml path sql query required default criteria singleton. (0.33 seconds)

Tip: Save time by hitting the return key instead of clicking on "search"

Data Access in ASP.NET 2.0

In addition, the proliferation of **XML** as a data store **required** extensive lines of ... Although the **default** SQLDependency class only supports Microsoft **SQL** ...msdn2.microsoft.com/en-us/library/ms379566.aspx - 51k - [Cached](#) - [Similar pages](#)

Chapter 1. Quickstart with Tomcat

The Cat.hbm.xml mapping file contains the metadata **required** for the ... You may also use Hibernate's direct **SQL query** feature or get a plain JDBC connection ...

www.hibernate.org/hib_docs/reference/en/html/quickstart.html - 29k -

[Cached](#) - [Similar pages](#)

Glossary « WordPress Codex

WordPress uses **query** strings to indicate **criteria** to search for specific posts ... of a class is created per request, this instance is a **singleton** object. ...codex.wordpress.org/Glossary - 105k - [Cached](#) - [Similar pages](#)

XQuery 1.0: An XML Query Language

The **XPath** and **XML Query** Test Suite is under development. ... If its operand is a **singleton** value of type xs:boolean or derived from xs:boolean, fn:boolean ...www.w3.org/TR/xquery/ - 826k - [Cached](#) - [Similar pages](#)

XML Path Language (XPath) 2.0

XPath 2.0 has been defined jointly by the **XML Query** Working Group (part of ... to specify conformance **criteria** for **XPath** in their respective environments. ...www.w3.org/TR/2002/WD-xpath20-20020816/ - 520k - [Cached](#) - [Similar pages](#)

[More results from www.w3.org]

Zend Developer Zone | Integrating Propel with the Zend Framework

So, if you amend your schema.xml file and restart the Propel build, ... classes in the **default**.properties file in the /_library/propel/generator **path**. ...devzone.zend.com/node/view/id/184 - 63k - [Cached](#) - [Similar pages](#)

IBM SJ 45-2 | DB2 goes hybrid: Integrating native XML and XQuery ...

as sql varchar(35). The xmlpattern **path** identifies the **XML** nodes to be indexed. ... In DB2, **XML** parsing is never **required** at **query** time, and indexes can be ...dx.doi.org/10.1147/sj.452.0271 - [Similar pages](#)

Tutorials

For webapp-deployments, this property is set via the web.xml file, ... **Criteria** and **Query** are the two components that help one implement this behavior in ...www.keelframework.org/docs/?q=book/print/3 - 33k - [Cached](#) - [Similar pages](#)

[PDF] ibms-45-02-14 271..298

File Format: PDF/Adobe Acrobat - [View as HTML](#)as sql varchar(35). The xmlpattern. **path** identifies the **XML** nodes to be indexed. It is called ... **XML** parsing is never **required** at **query** time, and ...www.research.ibm.com/journal/sj/452/beyer.pdf - [Similar pages](#)

[geeklog-cvs] Geeklog-2/system/DataAccess DAO.php, NONE, 1.1 ...

Previous message: [geeklog-cvs] Geeklog-2/sql NamedQueries.xml,NONE,1.1 ... \$xpath->query("/named_queries/query[@name='\$queryName']/criteria"); ...

<http://www.google.com/search?hl=en&lr=&q=xml+path+sql+query+required+default+criteria+singleton&...> 9/1/2006